



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/759,704	01/15/2004	Fang Yang	019287-0324127	8440
909 7590 05/03/2007 PILLSBURY WINTHROP SHAW PITTMAN, LLP P.O. BOX 10500 MCLEAN, VA 22102			EXAMINER PATEL, ASHOKKUMAR B	
			ART UNIT 2154	PAPER NUMBER
			MAIL DATE 05/03/2007	DELIVERY MODE PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 10/759,704	Applicant(s) YANG ET AL.	
	Examiner Ashok B. Patel	Art Unit 2154	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 05 April 2007.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-25 is/are pending in the application.
- 4a) Of the above claim(s) 2,7,10,15,18 and 23 is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1,3-6,8,9,11-14,16,17,19-22,24 and 25 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
 Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
 Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date <u>09/01/2006</u> . | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

1. Claims 1-25 are subject to examination. Claims 2, 7, 10, 15, 18 and 23 have been cancelled.

Continued Examination Under 37 CFR 1.114

2. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 04/05/2007 has been entered.

Response to Arguments

3. Applicant's arguments with respect to claims 1, 3- 6, 9, 11-14, 17, 19-22 and 25 have been considered but are moot in view of the new ground(s) of rejection.

Claim Rejections - 35 USC § 112

4. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

5. Claims 14 and 22 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Referring to claim 14,

Claim 14 recites the limitation "The software of Claim 1, wherein the hardware information includes chassis component information." There is insufficient antecedent basis for this limitation in the claim 1. Appropriate correction is required.

Referring to claim 22,

Claim 22 recites the limitation "The system of Claim 1," There is insufficient antecedent basis for this limitation in the claim 1. Appropriate correction is required.

Claim Rejections - 35 USC § 101

6. 35 U.S.C. 101 reads as follows:

Whoever invents or discovers any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof, may obtain a patent therefor, subject to the conditions and requirements of this title.

7. Claims 9, 11-13 and 16 are rejected under 35 U.S.C. 101 because the claimed invention is directed to non-statutory subject matter.

Referring to claim 9,

Claim 9 recites a " Software for monitoring hardware information associated with a plurality of distinct network devices in an enterprise system, the software comprising computer-readable instructions operable to:" in the preamble. At page 8, lines 18-21 of the instant specification contains intrinsic evidence as " Memory 120 may include any memory or data base module and may take the form of volatile or nonvolatile memory including, without limitation, magnetic media, optical media, random access memory (RAM), read-only memory (ROM), removable media, or any other suitable local or remote memory or storage component." As such, in the case of remote memory or

storage component, the software is merely electro-magnetic signals or carrier waves which do not fall into any of the four statutory categories set forth in the above statute.

Referring to claims 11-13 and 16,

Claims 11-13 and 16 are rejected for the reasons set forth for claim 9 because of their dependency on claim 9.

Claim Rejections - 35 USC § 102

9. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

10. Claims 1, 3, 5, 6, 8, 9, 11, 13, 14, 16, 17, 19, 21, 24 and 25 are rejected under 35 U.S.C. 102(b) as being anticipated by Kekic et al. (hereinafter Kekic)(US 5, 999, 179)

Referring to claim 1,

Kekic teaches a method for monitoring hardware information associated with a plurality of distinct network devices in an enterprise system (col. 43, line 28-47, "Managing Computer Network Elements Management activities performed by server 314 include: discovering elements on the network which may be managed; organizing the managed elements into groups; associating element managers with physical computer network elements; responding to alarms and reviewing an alarm log of exceptional network events; monitoring and controlling real-time network behavior by getting and setting MIB variables; using buttons to configure MIB variables with a single click; graphing real-time MIB variable values; tweaking rule definitions in order to hone

in on anomalous network behavior; and using a stand-alone MIB browser to manually manage elements without an EM or just to get MIB information.”), comprising:

invoking a flexible configuration file (col. 16, line 18-31, “Client-server network management system 375 is really two applications in one: a visual element manager builder and a manager. As explained more completely below, the visual element manager builder is a visual development environment in which device vendors or network managers may create standardized element management applications, called element managers. The manager provides the run-time environment in which the element managers may be executed to monitor and manage computer network behavior such as network throughput, collision rate, and number of duplicate IP packets, to name a few. No programming is required and the separation between the visual element manager and the manager is seamless and transparent to the user.”

Note: Client-server network management system 375 with “a visual element manger builder” building the “Fig. 3B” is the a flexible configuration file.) the flexible configuration file comprising a first location directive to retrieve parameters from a first network device and a second location directive to retrieve parameters from a second network device, the first network device comprising a first device type and the second network device comprising a second device type (col. 16, line 33-44, “According to the principles of this invention, one of a plurality of element managers 315 is associated with each managed computer network element in computer network 300, e.g., an element manager is associated with each of managed computer network elements 310 to 350. Herein, a management-enabled computer network element is any element in a computer network

Art Unit: 2154

that can be managed using a computer network management protocol, such as SNMP. A management-enabled computer network element can be any hardware or software on computer network 300 that implements the network management protocol by having a network management agent and a network management information database, or a similar process.”, Note: Please note that “one of a plurality of element managers 315 is associated with each managed computer network element in computer network 300, e.g., an element manager is associated with each of managed computer network elements 310 to 350.”, as such one of the plurality of element manager is “a first location directive to retrieve parameters from a first network device”, one of the plurality of element manager is “a second location directive to retrieve parameters from a second network device”, and it is evident that element 320 is “workstation” and 330 is BRIDGE, and therefore “the first network device comprising a first device type and the second network device comprising a second device type.”)

remotely retrieving (col. 21, line 23-30, “Managed element server 314 also interacts with managed element clients such as managed element server client 391 on portable personal computer 390, managed element server client 361 on personal computer 360, and managed element server client 371 on workstation 370. Multiple managed element clients can connect to managed element server 314, and can view and manipulate the plurality of managed element objects 415. Each of managed element server clients 361, 371 and 391 provides a graphic user-interface 375.”)real-time hardware information associated with the first network device based on the first location directive (col. 50, line 64-col. 51, line 13, “Monitoring and Controlling Real-time

Art Unit: 2154

Network Behavior The ability to monitor and control computer network 300 is fundamental to network configuration management. The values of MIB variables which have been associated with a component polling or trap event, as predefined in the element manager, may be displayed in a status panel whenever the event is detected on the network. The MIB variables, which have READ-WRITE access, may also be modified. The status panel for a component may be displayed only if monitoring for the managed computer network element was turned on when the computer network element was configured for management.”), the hardware information including information of one or more hardware characteristics (col. 16, line 33-44, “A management-enabled computer network element can be any hardware or software on computer network 300 that implements the network management protocol by having a network management agent and a network management information database, or a similar process.” Note: Please note in the above cited col. 50, line 64-col. 51, line 13, Status for “a component” is the “information of one or more hardware characteristics.”); and

dynamically presenting the real-time information through a display (col. 21, line 23-30, “Managed element server 314 also interacts with managed element clients such as managed element server client 391 on portable personal computer 390, managed element server client 361 on personal computer 360, and managed element server client 371 on workstation 370. Multiple managed element clients can connect to managed element server 314, and can view and manipulate the plurality of managed element objects 415. Each of managed element server clients 361, 371 and 391

Art Unit: 2154

provides a graphic user-interface 375.", the display including a first and a second window (Fig. 3), the first window including a hierarchical tree structure of user-selectable hardware characteristics (col. 23, line 39-49, "Navigation tree area 604, in this embodiment, displays a navigation tree 305 that is an object-oriented hierarchical representation of objects which represent (i) element managers and their attributes and (ii) managed elements and their attributes. Two alternative embodiments of managed element server 314 are possible. A first embodiment includes visual element manager builder 406, and a second embodiment does not include visual element manager builder 406. If visual element manager builder 406 is not included in server 314, element manager folder 641 is not displayed in navigation tree 305."), the second window including a tabular display of information associated with a hardware characteristic selected by a user in the hierarchical tree structure of the first window (Fig. 3, col. 24, line 48-54, col. 51, line 8-13, "To display the status panel for a component, the user right-clicks on the component node in navigation tree 305, or alternatively the component outline in element image area and selects Status from the resulting menu. In response to the selection of Status, a status panel such as status panel 3300 (FIG. 33) is displayed.")

Referring to claim 3,

Kekic teaches the method of Claim 25, the hardware information comprising chassis component information (Fig. 3A, col. 16, line 39-44, 51-60, "According to the principles of this invention, one of a plurality of element managers 315 is associated with each managed computer network element in computer network 300, e.g., an

Art Unit: 2154

element manager is associated with each of managed computer network elements 310 to 350. Herein, a management-enabled computer network element is any element in a computer network that can be managed using a computer network management protocol, such as SNMP. A management-enabled computer network element can be any hardware or software on computer network 300 that implements the network management protocol by having a network management agent and a network management information database, or a similar process.”, col. 18, line 19-32, “A poll event in a managed element object contains information on a set of attributes that need to be polled, a default polling interval, a current polling interval that is being used, and a set of flags that are used to determine if polling is turned on or off for the event, and if the polling results are to be logged. The poll event also contains a list of states and an associated polling interval for each state. A poll event is processed by the poll server only when the managed element component associated with the poll event is in one of the listed states. The primary purpose of states is to classify the status of a component. States may also serve as transition points between changes in modes of operation of a component.” Note: The difference between “managed element component associated with the poll event” and “network element is any element in a computer network that can be managed using a computer network management protocol.”)

Referring to claim 5,

Kekic teaches the method of Claim 25, further comprising selecting a second location directive of the flexible configuration file to retrieve hardware information associated with a second of the network devices (col. 16, line 33-44, “According to the

Art Unit: 2154

principles of this invention, one of a plurality of element managers 315 is associated with each managed computer network element in computer network 300, e.g., an element manager is associated with each of managed computer network elements 310 to 350. Herein, a management-enabled computer network element is any element in a computer network that can be managed using a computer network management protocol, such as SNMP. A management-enabled computer network element can be any hardware or software on computer network 300 that implements the network management protocol by having a network management agent and a network management information database, or a similar process.”, Note: Please note that “one of a plurality of element managers 315 is associated with each managed computer network element in computer network 300, e.g., an element manager is associated with each of managed computer network elements 310 to 350.”, as such one of the plurality of element manager is “a first location directive to retrieve parameters from a first network device”, one of the plurality of element manager is “a second location directive to retrieve parameters from a second network device”, and it is evident that element 320 is “workstation” and 330 is BRIDGE, and therefore “the first network device comprising a first device type and the second network device comprising a second device type.”).

Referring to claim 6,

Kekic teaches the method of Claim 1, further comprising:

polling the particular network device based on a polling configuration file, the polling configuration file comprising an associated polling interval for each hardware characteristic (col. 18, line 12-32, “Poll server 417 creates a thread for each polling

Art Unit: 2154

event (request) specified in poll events of managed element object 416. Poll server 417 also performs single network management operations. When poll server 417 receives a response to polling event, the data in the response is passed to event engine 418 for evaluation. Poll server 427 performs similar operations for managed element object 426. A poll event in a managed element object contains information on a set of attributes that need to be polled, a default polling interval, a current polling interval that is being used, and a set of flags that are used to determine if polling is turned on or off for the event, and if the polling results are to be logged. The poll event also contains a list of states and an associated polling interval for each state. A poll event is processed by the poll server only when the managed element component associated with the poll event is in one of the listed states. The primary purpose of states is to classify the status of a component. States may also serve as transition points between changes in modes of operation of a component.", and col. 20, line 14-34, "States s1, s2, s3, and s4 are the states that the component can possibly have. Polling events p1, p2, and p3 are user defined. Polling event p1 is performed in either states s1 or s2. Polling event p2 is performed only if the component is in state s3, and polling event p3 is performed only if the component is in state s4. Here, a polling event is performed by polling the component. The user can specify, using client 391, different polling intervals for polling event p1 in states s1 and s2. Polling event rules p1r1, p1r2, and p1r3 are user-configured rules for polling event p1. Polling event rule p1r1 is picked to evaluate the polling result of polling event p1 when the component is in state s1, i.e., polling event rule p1r1 has a requisite state of state s1. Polling event rules p1r2 and p1r3 are used to

Art Unit: 2154

evaluate the polling result when the component is in state s2. If the condition of polling event rule p1r2 is evaluated true, the component transitions from state s2 to state s3. Hence, since polling event rule p1r3 is evaluated only when the component is in state s2, polling event rule p1r3 is not evaluated. Polling event rules p2r1 and p3r1 are rules defined for polling events p2 and p3 respectively.”);

receiving updated hardware information associated with the network device at each associated polling interval (col. 20, line 14-34, “States s1, s2, s3, and s4 are the states that the component can possibly have. Polling events p1, p2, and p3 are user defined. Polling event p1 is performed in either states s1 or s2. Polling event p2 is performed only if the component is in state s3, and polling event p3 is performed only if the component is in state s4. Here, a polling event is performed by polling the component. The user can specify, using client 391, different polling intervals for polling event p1 in states s1 and s2. Polling event rules p1r1, p1r2, and p1r3 are user-configured rules for polling event p1. Polling event rule p1r1 is picked to evaluate the polling result of polling event p1 when the component is in state s1, i.e., polling event rule p1r1 has a requisite state of state s1. Polling event rules p1r2 and p1r3 are used to evaluate the polling result when the component is in state s2. If the condition of polling event rule p1r2 is evaluated true, the component transitions from state s2 to state s3. Hence, since polling event rule p1r3 is evaluated only when the component is in state s2, polling event rule p1r3 is not evaluated. Polling event rules p2r1 and p3r1 are rules defined for polling events p2 and p3 respectively.”); and

dynamically displaying the updated hardware information(Fig. 3, col. 21, line 23-30, "Managed element server 314 also interacts with managed element clients such as managed element server client 391 on portable personal computer 390, managed element server client 361 on personal computer 360, and managed element server client 371 on workstation 370. Multiple managed element clients can connect to managed element server 314, and can view and manipulate the plurality of managed element objects 415. Each of managed element server clients 361, 371 and 391 provides a graphic user-interface 375.")

Referring to claim 8,

Kekic teaches the method of Claim 25, the interactive display (col. 21, line 23-30, "Managed element server 314 also interacts with managed element clients such as managed element server client 391 on portable personal computer 390, managed element server client 361 on personal computer 360, and managed element server client 371 on workstation 370. Multiple managed element clients can connect to managed element server 314, and can view and manipulate the plurality of managed element objects 415. Each of managed element server clients 361, 371 and 391 provides a graphic user-interface 375."),comprising a first and a second window (Fig. 3), the first window comprising a hierarchical tree structure of hardware characteristics (col. 23, line 39-49, "Navigation tree area 604, in this embodiment, displays a navigation tree 305 that is an object-oriented hierarchical representation of objects which represent (i) element managers and their attributes and (ii) managed elements and their attributes. Two alternative embodiments of managed element server 314 are possible. A first

Art Unit: 2154

embodiment includes visual element manager builder 406, and a second embodiment does not include visual element manager builder 406. If visual element manager builder 406 is not included in server 314, element manager folder 641 is not displayed in navigation tree 305.”), the second window comprising a tabular display of information associated with a hardware characteristic selected in the hierarchical tree structure (col. 24, line 48-54, col. 51, line 8-13, “To display the status panel for a component, the user right-clicks on the component node in navigation tree 305, or alternatively the component outline in element image area and selects Status from the resulting menu. In response to the selection of Status, a status panel such as status panel 3300 (FIG. 33) is displayed.”)

Referring to claim 9,

Kekic teaches Software for monitoring hardware information associated with a plurality of distinct network devices in an enterprise system (col. 14, line 8-26, “According to the principles of this invention, a managed element server 314 (FIG. 3A) was developed as a comprehensive open, standards-based network management solution for computer networks having a computer network management capability, such as SNMP. Managed element server 314 of this invention efficiently manages a constantly changing and growing computer network 300 which is composed of a wide array of heterogeneous elements, e.g., operating system server 310, which in one embodiment is a Microsoft WINDOWS NT server, workstation 320, which could be for example a DEC, Sun Microsystems, or Silicon Graphics workstation, bridge 330, router 340, and printer 350, that are produced by different vendors, and that support many

Art Unit: 2154

different platform types. (WINDOWS NT is a registered U.S. trademark of Microsoft Corp. of Redmond, Wash.) The solution of this invention, as described more completely below, is flexible, robust, secure, collaborative, and most importantly works.”), the software comprising computer-readable instructions operable to:

invoking a flexible configuration file (col. 16, line 18-31, “Client-server network management system 375 is really two applications in one: a visual element manager builder and a manager. As explained more completely below, the visual element manager builder is a visual development environment in which device vendors or network managers may create standardized element management applications, called element managers. The manager provides the run-time environment in which the element managers may be executed to monitor and manage computer network behavior such as network throughput, collision rate, and number of duplicate IP packets, to name a few. No programming is required and the separation between the visual element manager and the manager is seamless and transparent to the user.”

Note: Client-server network management system 375 with “a visual element manger builder” building the “Fig. 3B” is the a flexible configuration file.) the flexible configuration file comprising a first location directive to retrieve parameters from a first network device and a second location directive to retrieve parameters from a second network device, the first network device comprising a first device type and the second network device comprising a second device type (col. 16, line 33-44, “According to the principles of this invention, one of a plurality of element managers 315 is associated with each managed computer network element in computer network 300, e.g., an element manager is

Art Unit: 2154

associated with each of managed computer network elements 310 to 350. Herein, a management-enabled computer network element is any element in a computer network that can be managed using a computer network management protocol, such as SNMP. A management-enabled computer network element can be any hardware or software on computer network 300 that implements the network management protocol by having a network management agent and a network management information database, or a similar process.”, Note: Please note that “one of a plurality of element managers 315 is associated with each managed computer network element in computer network 300, e.g., an element manager is associated with each of managed computer network elements 310 to 350.”, as such one of the plurality of element manager is “a first location directive to retrieve parameters from a first network device”, one of the plurality of element manager is “a second location directive to retrieve parameters from a second network device”, and it is evident that element 320 is “workstation” and 330 is BRIDGE, and therefore “the first network device comprising a first device type and the second network device comprising a second device type.”)

remotely retrieving (col. 21, line 23-30, “Managed element server 314 also interacts with managed element clients such as managed element server client 391 on portable personal computer 390, managed element server client 361 on personal computer 360, and managed element server client 371 on workstation 370. Multiple managed element clients can connect to managed element server 314, and can view and manipulate the plurality of managed element objects 415. Each of managed element server clients 361, 371 and 391 provides a graphic user-interface 375.”)real-

Art Unit: 2154

time hardware information associated with the first network device based on the first location directive (col. 50, line 64-col. 51, line 13, "Monitoring and Controlling Real-time Network Behavior The ability to monitor and control computer network 300 is fundamental to network configuration management. The values of MIB variables which have been associated with a component polling or trap event, as predefined in the element manager, may be displayed in a status panel whenever the event is detected on the network. The MIB variables, which have READ-WRITE access, may also be modified. The status panel for a component may be displayed only if monitoring for the managed computer network element was turned on when the computer network element was configured for management."), the hardware information including information of one or more hardware characteristics (col. 16, line 33-44, "A management-enabled computer network element can be any hardware or software on computer network 300 that implements the network management protocol by having a network management agent and a network management information database, or a similar process." Note: Please note in the above cited col. 50, line 64-col. 51, line 13, Status for "a component" is the "information of one or more hardware characteristics."); and

dynamically presenting the real-time information through a display (col. 21, line 23-30, "Managed element server 314 also interacts with managed element clients such as managed element server client 391 on portable personal computer 390, managed element server client 361 on personal computer 360, and managed element server client 371 on workstation 370. Multiple managed element clients can connect to

Art Unit: 2154

managed element server 314, and can view and manipulate the plurality of managed element objects 415. Each of managed element server clients 361, 371 and 391 provides a graphic user-interface 375.", Fig. 3),

poll the particular network device based on a polling configuration file, the polling configuration file comprising an associated polling interval for each hardware characteristic (col. 18, line 12-32, "Poll server 417 creates a thread for each polling event (request) specified in poll events of managed element object 416. Poll server 417 also performs single network management operations. When poll server 417 receives a response to polling event, the data in the response is passed to event engine 418 for evaluation. Poll server 427 performs similar operations for managed element object 426. A poll event in a managed element object contains information on a set of attributes that need to be polled, a default polling interval, a current polling interval that is being used, and a set of flags that are used to determine if polling is turned on or off for the event, and if the polling results are to be logged. The poll event also contains a list of states and an associated polling interval for each state. A poll event is processed by the poll server only when the managed element component associated with the poll event is in one of the listed states. The primary purpose of states is to classify the status of a component. States may also serve as transition points between changes in modes of operation of a component.", and col. 20, line 14-34, "States s1, s2, s3, and s4 are the states that the component can possibly have. Polling events p1, p2, and p3 are user defined. Polling event p1 is performed in either states s1 or s2. Polling event p2 is performed only if the component is in state s3, and polling event p3 is performed only if

Art Unit: 2154

the component is in state s4. Here, a polling event is performed by polling the component. The user can specify, using client 391, different polling intervals for polling event p1 in states s1 and s2. Polling event rules p1r1, p1r2, and p1r3 are user-configured rules for polling event p1. Polling event rule p1r1 is picked to evaluate the polling result of polling event p1 when the component is in state s1, i.e., polling event rule p1r1 has a requisite state of state s1. Polling event rules p1r2 and p1r3 are used to evaluate the polling result when the component is in state s2. If the condition of polling event rule p1r2 is evaluated true, the component transitions from state s2 to state s3. Hence, since polling event rule p1r3 is evaluated only when the component is in state s2, polling event rule p1r3 is not evaluated. Polling event rules p2r1 and p3r1 are rules defined for polling events p2 and p3 respectively.”);

receive updated hardware information associated with the network device at each associated polling interval (col. 20, line 14-34, “States s1, s2, s3, and s4 are the states that the component can possibly have. Polling events p1, p2, and p3 are user defined. Polling event p1 is performed in either states s1 or s2. Polling event p2 is performed only if the component is in state s3, and polling event p3 is performed only if the component is in state s4. Here, a polling event is performed by polling the component. The user can specify, using client 391, different polling intervals for polling event p1 in states s1 and s2. Polling event rules p1r1, p1r2, and p1r3 are user-configured rules for polling event p1. Polling event rule p1r1 is picked to evaluate the polling result of polling event p1 when the component is in state s1, i.e., polling event rule p1r1 has a requisite state of state s1. Polling event rules p1r2 and p1r3 are used to

evaluate the polling result when the component is in state s2. If the condition of polling event rule p1r2 is evaluated true, the component transitions from state s2 to state s3. Hence, since polling event rule p1r3 is evaluated only when the component is in state s2, polling event rule p1r3 is not evaluated. Polling event rules p2r1 and p3r1 are rules defined for polling events p2 and p3 respectively."); and

dynamically displaying the updated hardware information(Fig. 3, col. 21, line 23-30, "Managed element server 314 also interacts with managed element clients such as managed element server client 391 on portable personal computer 390, managed element server client 361 on personal computer 360, and managed element server client 371 on workstation 370. Multiple managed element clients can connect to managed element server 314, and can view and manipulate the plurality of managed element objects 415. Each of managed element server clients 361, 371 and 391 provides a graphic user-interface 375.")

Referring to claim 11,

Kekic teaches the software of Claim 9, the hardware information comprising chassis component information (Fig. 3A, col. 16, line 39-44, 51-60, "According to the principles of this invention, one of a plurality of element managers 315 is associated with each managed computer network element in computer network 300, e.g., an element manager is associated with each of managed computer network elements 310 to 350. Herein, a management-enabled computer network element is any element in a computer network that can be managed using a computer network management protocol, such as SNMP. A management-enabled computer network element can be

Art Unit: 2154

any hardware or software on computer network 300 that implements the network management protocol by having a network management agent and a network management information database, or a similar process.”, col. 18, line 19-32, “A poll event in a managed element object contains information on a set of attributes that need to be polled, a default polling interval, a current polling interval that is being used, and a set of flags that are used to determine if polling is turned on or off for the event, and if the polling results are to be logged. The poll event also contains a list of states and an associated polling interval for each state. A poll event is processed by the poll server only when the managed element component associated with the poll event is in one of the listed states. The primary purpose of states is to classify the status of a component. States may also serve as transition points between changes in modes of operation of a component.” Note: The difference between “managed element component associated with the poll event” and “network element is any element in a computer network that can be managed using a computer network management protocol.”)

Referring to claim 13,

Kekic teaches the software of Claim 9, further operable to select a second location directive of the flexible configuration file to retrieve hardware information associated with a second of the network devices (col. 16, line 33-44, “According to the principles of this invention, one of a plurality of element managers 315 is associated with each managed computer network element in computer network 300, e.g., an element manager is associated with each of managed computer network elements 310 to 350. Herein, a management-enabled computer network element is any element in a

Art Unit: 2154

computer network that can be managed using a computer network management protocol, such as SNMP. A management-enabled computer network element can be any hardware or software on computer network 300 that implements the network management protocol by having a network management agent and a network management information database, or a similar process.”, Note: Please note that “one of a plurality of element managers 315 is associated with each managed computer network element in computer network 300, e.g., an element manager is associated with each of managed computer network elements 310 to 350.”, as such one of the plurality of element manager is “a first location directive to retrieve parameters from a first network device”, one of the plurality of element manager is “a second location directive to retrieve parameters from a second network device”, and it is evident that element 320 is “workstation” and 330 is BRIDGE, and therefore “the first network device comprising a first device type and the second network device comprising a second device type.”).

Referring to claim 14,

Kekic teaches the software of Claim 1, wherein the hardware information includes chassis component information (Fig. 3A, col. 16, line 39-44, 51-60, “According to the principles of this invention, one of a plurality of element managers 315 is associated with each managed computer network element in computer network 300, e.g., an element manager is associated with each of managed computer network elements 310 to 350. Herein, a management-enabled computer network element is any element in a computer network that can be managed using a computer network management protocol, such as SNMP. A management-enabled computer network

element can be any hardware or software on computer network 300 that implements the network management protocol by having a network management agent and a network management information database, or a similar process.”, col. 18, line 19-32, “A poll event in a managed element object contains information on a set of attributes that need to be polled, a default polling interval, a current polling interval that is being used, and a set of flags that are used to determine if polling is turned on or off for the event, and if the polling results are to be logged. The poll event also contains a list of states and an associated polling interval for each state. A poll event is processed by the poll server only when the managed element component associated with the poll event is in one of the listed states. The primary purpose of states is to classify the status of a component. States may also serve as transition points between changes in modes of operation of a component.” Note: The difference between “managed element component associated with the poll event” and “network element is any element in a computer network that can be managed using a computer network management protocol.”)

Referring to claim 16,

Kekic teaches the software of Claim 9, the interactive display (col. 21, line 23-30, “Managed element server 314 also interacts with managed element clients such as managed element server client 391 on portable personal computer 390, managed element server client 361 on personal computer 360, and managed element server client 371 on workstation 370. Multiple managed element clients can connect to managed element server 314, and can view and manipulate the plurality of managed element objects 415. Each of managed element server clients 361, 371 and 391

Art Unit: 2154

provides a graphic user-interface 375."), comprising a first and a second window (Fig. 3), the first window comprising a hierarchical tree structure of hardware characteristics (col. 23, line 39-49, "Navigation tree area 604, in this embodiment, displays a navigation tree 305 that is an object-oriented hierarchical representation of objects which represent (i) element managers and their attributes and (ii) managed elements and their attributes. Two alternative embodiments of managed element server 314 are possible. A first embodiment includes visual element manager builder 406, and a second embodiment does not include visual element manager builder 406. If visual element manager builder 406 is not included in server 314, element manager folder 641 is not displayed in navigation tree 305."), the second window comprising a tabular display of information associated with a hardware characteristic selected in the hierarchical tree structure (col. 24, line 48-54, col. 51, line 8-13, "To display the status panel for a component, the user right-clicks on the component node in navigation tree 305, or alternatively the component outline in element image area and selects Status from the resulting menu. In response to the selection of Status, a status panel such as status panel 3300 (FIG. 33) is displayed."

Referring to claim 17,

Claim 17 is a claim to a system for monitoring information associated with a network element in accordance with the instructions of claim 9. Therefore, claim 17 is rejected for the reasons set forth for claim 9. (please note col. 87, line 27-31 for MIB. Sever OS server hosts Element Manager Server, as such memory and processors are part of the system.)

Art Unit: 2154

Referring to claim 19,

Claim 19 is a claim to a system for monitoring information associated with a network element in accordance with the instructions of claim 11. Therefore, claim 17 is rejected for the reasons set forth for claim 11.

Referring to claim 21,

Claim 21 is a claim to a system for monitoring information associated with a network element in accordance with the instructions of claim 13. Therefore, claim 21 is rejected for the reasons set forth for claim 13.

Referring to claim 24,

Claim 24 is a claim to a system for monitoring information associated with a network element in accordance with the instructions of claim 16. Therefore, claim 24 is rejected for the reasons set forth for claim 16.

Referring to claim 25,

Claim 25 is a method for monitoring hardware information associated with a plurality of distinct network devices in an enterprise system in accordance with the instructions of claim 9. Therefore, claim 25 is rejected for the reasons set forth for claim 9.

Claim Rejections - 35 USC § 103

11. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Art Unit: 2154

12. Claims 4, 12, 20 and 22 are rejected under 35 U.S.C. 103(a) as being Unpatentable over Kekic et al. (hereinafter Kekic)(US 5, 999, 179) in view of Fung (US 2003/0200473 A1)

Referring to claim 4,

Kekic teaches the method of Claim 25, each hardware characteristic selected from the group consisting of memory usage (col. 23, line 34-38, col. 25, line 5-10); Central Processing Unit (CPU) usage (col. 23, line 34-28) and power supply status (col. 27, line 10-15), however fails to teach fan status and module card status.

Fung teaches the method of claim 1, each hardware characteristic selected from the group consisting of: memory usage (page 29, Table III, page 20, para.[190]); chassis temperature (page 8, para.[0079]); Central Processing Unit (CPU) usage (page 12, para.[107]); fan status (page 15, para.[0142], page 16, para.[0154]); module card status (page 15, para.[0144], page 16, para. [00147]); and power supply status. (page 15, para. [0143]).

Therefore it would have been an obvious to one of an ordinary skill in art, having the teachings of Kekic and Fung in front of him at the time of invention was made, to include all these parameters be monitored for each of the devices by configuring the Element Manger for these "components" suggested by Kekic.

It would have been obvious because Kekic gives build up technology for each of the desired devices on the network to be monitored along with to be monitored "component" while Fung just shows what to monitor with suggesting that these

Art Unit: 2154

parameters can also be retrieved through the industry's standard SNMP MIB, which is completely acceptable and implemental for Kekic.

Referring to claim 12,

Kekic teaches the software of Claim 9, each hardware characteristic selected from the group consisting of memory usage (col. 23, line 34-38, col. 25, line 5-10); Central Processing Unit (CPU) usage (col. 23, line 34-28) and power supply status (col. 27, line 10-15), however fails to teach fan status and module card status.

Fung teaches the method of claim 1, each hardware characteristic selected from the group consisting of: memory usage (page 29, Table III, page 20, para.[190]); chassis temperature (page 8, para.[0079]); Central Processing Unit (CPU) usage (page 12, para.[107]); fan status (page 15, para.[0142], page 16, para.[0154]); module card status (page 15, para.[0144], page 16, para. [00147]); and power supply status. (page 15, para. [0143]).

Therefore it would have been an obvious to one of an ordinary skill in art, having the teachings of Kekic and Fung in front of him at the time of invention was made, to include all these parameters be monitored for each of the devices by configuring the Element Manger for these "components" suggested by Kekic.

It would have been obvious because Kekic gives build up technology for each of the desired devices on the network to be monitored along with to be monitored "component" while Fung just shows what to monitor with suggesting that these parameters can also be retrieved through the industry's standard SNMP MIB, which is completely acceptable and implemental for Kekic.

Referring to claim 20,

Claim 20 is a claim to a system for monitoring information associated with a network element in accordance with the instructions of claim 12. Therefore, claim 20 is rejected for the reasons set forth for claim 12.

Referring to claim 22,

Claim 22 is a claim to a system for monitoring information associated with a network element in accordance with the instructions of claim 12. Therefore, claim 22 is rejected for the reasons set forth for claim 12.

Conclusion

Examiner's note: Examiner has cited particular columns and line numbers in the references as applied to the claims above for the convenience of the applicant. Although the specified citations are representative of the teachings of the art and are applied to the specific limitations within the individual claim, other passages and figures may apply as well. It is respectfully requested from the applicant in preparing responses, to fully consider the references in entirety as potentially teaching all or part of the claimed invention, as well as the context of the passage as taught by the prior art or disclosed by the Examiner.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Ashok B. Patel whose telephone number is (571) 272-3972. The examiner can normally be reached on 6:30 am-4:30 pm.

Art Unit: 2154

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Nathan A. Flynn can be reached on (571) 272-1915. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.



Ashok B. Patel
Examiner
Art Unit 2154
